

LIQUID[®] DRIVEWAY

100% Acrylic Blacktop Coating

Manufacturer:

ThorWorks Industries, Inc.
2520 S. Campbell St.
Sandusky, OH 44870
Phone: 800-326-1994
Fax: 419-626-5477

Description

Liquid Driveway is a 100% Acrylic Driveway Coating fortified with sand for added slip-resistance and durability. Formulated for blacktop driveways, Liquid Driveway provides superior protection from the elements as well as a rich, jet-black appearance to your driveway. Scuff-free, non-tracking finish helps keep floors clean and provides for cleaner outdoor play. Liquid Driveway is packaged in an oversized pail to provide extra space for dipping roller and moving without spillage.

Uses

Beautifies and protects asphalt pavement surfaces including driveways, walkways, and more.

Coverage

Smooth Asphalt - Up To 600 square feet/pail
Moderate Asphalt - Up to 450 square feet/pail
Porous Asphalt - Up to 300 square feet/pail

Directions

CLEAN SURFACE- Sweep all dirt and loose debris from driveway surface. Trim any grass or weeds growing over surface. Scrub all oil and gasoline stains with household detergent and water. Hose off driveway surface with water and allow to dry.

APPLYING ULTRA GLOSS SEALER- Repair any cracks with suitable crack filler. Stir pail thoroughly. Apply coating with roller in 4'X4' sections rolling in perpendicular strokes to achieve better coverage. Do not dilute product, or mix with other driveway coatings. For optimum durability and warranty purposes, apply two coats.

Drying Time

Allow first coat to dry completely before applying a second coat. Allow four hours before light foot traffic, and 24 hours before vehicle traffic.

Clean Up

Wash tools with water before material dries.

Important

Read entire label before using. Application temperature must be a minimum of 50 °F and rising. Do not apply when temperature is expected to drop below 60 °F within a 24 hour period, or exceed 90 °F. Be sure to wear eye protection, gloves, long pants, and long sleeves when mixing and applying Liquid Driveway materials. In areas where dew or fog accumulates in the early evening, it is best to coat in the morning. Stop coating by early afternoon (3:00 pm) to prevent wash off, which will occur if dew, fog, or rain arrive before coating dries. Do not apply if rain is imminent or forecast within 24 hours of application.

Precautions

- Do Not Heat Or Thin
- Do Not Freeze
- Do Not Store At Temperatures Below 50 °F

Safety And Environmental Precautions

- Refer To Material Safety Data Sheet Before Using
- For Exterior Use Only
- Apply In A Well Ventilated Area
- Close Container When Not In Use
- Environmental Information Is On The Material Safety Data Sheet
- Do Not Reuse Empty Container
- Volatile Organic Content (VOC) Is less than 50 Gm/Liter Max
- Keep Out Of Reach Of Children
- Avoid Breathing Vapors And Contact With Eyes And Skin. Do Not Take Internally
- Wear Eye Protection And Gloves When Applying

Ingredients:	CAS No.
Acrylic Polymer	Proprietary
Silica Sand	14808-60-7
Water	7732-18-5
Carbon Black	1333-86-4
Inert Mineral Filler	N/A

Liquid Driveway - 100% Acrylic Blacktop Coating

Revised: 07/11