

# Dry Seal

Premium Rubberized Foundation Coating



## Manufacturer:

ThorWorks Industries, Inc.  
2520 S. Campbell St.  
Sandusky, OH 44870  
Phone: 800-326-1994  
Fax: 419-626-5477

## Description

An elastomeric polymer modified asphalt emulsion designed for coating concrete foundations. Protects concrete foundations from moisture and water intrusion. Dries black.

## Uses

- Waterproofing Exterior Concrete
- Basement Walls
- Poured Concrete Walls
- Polystyrene/Styrofoam Insulation Board
- Wood, Foam & More

## Surface Preparation

For best results, surface shall be clean, dry and free of any dirt or contaminants.

## Application

Stir container thoroughly. Apply using either a brush or airless spray unit (suggested tip size .021 to .025). Apply material at a rate of 150 square feet per 4.75 gallon pail. Allow material to dry and cure for 24 hours prior to application of foam or drainage boards or backfilling.

## Drying Time

Allow 24 hours depending on weather conditions.

## Clean Up

While wet, use soap and water.

## Weather Conditions

- Application temperature must be a minimum of 60 °F and rising. Do not apply when temperature is expected to drop below 50 °F within a 24- hour period.
- In areas where dew or fog accumulates in the early evening, it is best to coat in the morning. Stop coating by early afternoon (3:00 pm) to prevent wash off, which will occur if dew, fog, or rain arrives before coating dries.
- Do not apply if rain is imminent or forecast within 24 hours of application.

## Coverage (Approximate)

- Approximately 30 square feet per gallon pail at 60 mils thickness.

## Precautions

- Do Not Freeze
- Do Not Store At Temperatures Below 50 °F

## Safety And Environmental Precautions

- Refer To Material Safety Data Sheet Before Using
- For Exterior Application Only
- Close Container When Not In Use
- Environmental Information Is On The Material Safety Data Sheet
- Do Not Reuse Empty Container
- Volatile Organic Content (VOC) Is 0 gm/liter max
- KEEP OUT OF REACH OF CHILDREN

Ingredients:	Cas No.
Water	7732-18-5
Polymer	N/A
Asphalt	8052-42-4

Dry Seal - Premium Rubberized Foundation Coating

Revised: 03/08