

Shingle Saver Clear Roof Coating

100% Acrylic Elastomeric Roof Coating



Manufacturer:

ThorWorks Industries, Inc.
2520 S. Campbell St.
Sandusky, OH 44870
Phone: 800-326-1994
Fax: 419-626-5477

Description

Shingle Saver is a clear drying 100% Acrylic Elastomeric Roof Coating designed to renew and protect asphalt, fiberglass, and Slate Shingles.

Uses

ROOF SURFACES: Asphalt, Fiberglass, Slate Shingles

WALL SURFACES: Concrete, Brick, Stucco, Exposed Aggregate, Decorative Stone and Wood.

Coverage

Approximately 100-200 square feet per gallon depending on surface porosity.

Directions

CLEAN AND REPAIR ROOF- Sweep off all dirt, dust, and debris. Remove mildew, oil, grease, or other foreign material on the surface. Remove mold and mildew with SealBest Concentrated Roof Cleaner or bleach solution (1 part chlorine bleach and 3 parts water). Rinse thoroughly and allow to dry.

APPLYING ROOF COATING- Stir pail thoroughly. Do not dilute. Apply with a 1/2" nap roller, soft bristle paint brush or airless type sprayer (tip size .01 - .015). For optimum performance and durability apply a second coat after first coat has thoroughly dried.

Drying Time

Dependent upon weather conditions, typically 1-4 hours.

Clean Up

Clean tools with water before material has dried.

Important

Read entire label before using. Application temperature must be a minimum of 60 °F and rising. Do not apply when temperature is expected to drop below 50 °F within a 24 hour period. Be sure to wear eye protection, gloves, long pants, and long sleeves when mixing and applying SealBest materials. In areas where dew or fog accumulates in the early evening, it is best to coat in the morning. Stop coating by early afternoon (3:00 pm) to prevent wash off, which will occur if dew, fog, or rain arrive before coating dries. Do not apply if rain is imminent or forecast within 24 hours of application.

Precautions

- Do Not Heat Or Thin
- Do Not Freeze
- Do Not Store At Temperatures Below 50 °F

Safety And Environmental Precautions

- Refer To Material Safety Data Sheet Before Using
- For Exterior Use Only
- Apply In A Well Ventilated Area
- Close Container When Not In Use
- Environmental Information Is On The Material Safety Data Sheet
- Do Not Reuse Empty Container
- Volatile Organic Content (VOC) Is 55 Gm/Liter Max
- Keep Out Of Reach Of Children
- Avoid Breathing Vapors And Contact With Eyes And Skin. Do Not Take Internally
- Wear Eye Protection And Gloves When Applying

Ingredients:	CAS No.
Water	7732-18-5
100% Acrylic Emulsion Polymer	Proprietary

Shingle Saver - Clear Roof Coating

Revised: 01/11