

Acrylic One-Step Fiber Mesh Reinforced Roof Patch

Superior Reinforcement and Strength



Manufacturer:

ThorWorks Industries, Inc.
2520 S. Campbell St.
Sandusky, OH 44870
Phone: 800-326-1994
Fax: 419-626-5477

Description

One-Step Roof Patch is an acrylic fiber mesh reinforced patching material that exhibits outstanding strength and flexibility. One-Step eliminates the need for the use of fabric. One-Step's unique fiber mesh modification provides superior reinforcement and strength as compared to roof patches utilizing standard fabric.

Uses

One-Step is ideal for repairing cracks, seams, flashings, vent pipes, chimneys, skylights, and more.

Coverage

One-gallon pail will cover approximately 9 square feet of roof surface when applied at 3/16" thick.

Directions

CLEAN AND REPAIR ROOF- Sweep off all dirt, dust, and debris. Remove rust, mildew, oil, grease, or other foreign material on the surface. Scrub roof with solution of TSP (Trisodium Phosphate) and water. Remove mold and mildew with bleach solution (1 part chlorine bleach and 3 parts water). Rinse thoroughly and allow to dry. Areas holding water lasting 2-3 days must be repaired using roof drains or other corrective drainage measures.

APPLYING ROOF PATCH- Stir pail thoroughly. Apply One-Step Roof Patch with a trowel or putty knife to a depth of at least 3/16" deep. Trowel smooth.

Drying Time

Dependent upon weather conditions.

Clean Up

Clean tools with water before material has dried.

Important

Read entire label before using. Application temperature must be a minimum of 60 °F and rising. Do not apply when temperature is expected to drop below 50 °F within a 24 hour period. Be sure to wear eye protection, gloves, long pants, and

long sleeves when mixing and applying SealBest materials. In areas where dew or fog accumulates in the early evening, it is best to coat in the morning. Stop coating by early afternoon (3:00 pm) to prevent wash off, which will occur if dew, fog, or rain arrive before coating dries. Do not apply if rain is imminent or forecast within 24 hours of application.

Precautions

- Do Not Heat Or Thin
- Do Not Freeze
- Do Not Store At Temperatures Below 50 °F

Safety And Environmental Precautions

- Refer To Material Safety Data Sheet Before Using
- For Exterior Use Only
- Apply In A Well Ventilated Area
- Close Container When Not In Use
- Environmental Information Is On The Material Safety Data Sheet
- Do Not Reuse Empty Container
- Volatile Organic Content (VOC) Is Less Than 100 Gm/Liter Max
- Keep Out Of Reach Of Children
- Avoid Breathing Vapors And Contact With Eyes And Skin. Do Not Take Internally
- Wear Eye Protection And Gloves When Applying

Ingredients:	CAS No.
Water	7732-18-5
Acrylic Emulsion Polymer	Proprietary
Calcium Carbonate	16389-88-1
Synthetic Fiber	Proprietary

Acrylic One-Step Fiber Mesh Reinforced Roof Patch

Revised: 01/11