



Acrylic Clear-Drying Roof Patch

100% acrylic

Manufacturer:

ThorWorks Industries, Inc.
2520 S. Campbell St.
Sandusky, OH 44870
Phone: 800-326-1994
Fax: 419-626-5477

Description

100% acrylic elastomeric water-based clear-drying roof patch. SealBest Acrylic Clear Drying Roof Patch meets ASTM C920, Type S, NS (Non-Sag), Class 25.

Uses

- Adhering Shingles
- Repairing Cracks And Seams
- Flashings, Vents, Gutters, Skylights, Air Conditioners

Surface Preparation

Clean Roof - Remove dust, dirt, debris, mildew and other contaminants from surface.

Application

Application temperature must be a minimum of 60°F and rising. Do not apply when temperature is expected to drop below 60°F within a 24 hour period. In areas where dew or fog accumulates in the early evening, it is best to coat in the morning. Stop coating by early afternoon (3:00 pm) to prevent wash off, which will occur if dew, fog, or rain arrives before coating dries. Apply Roof Patch with a trowel or putty knife.

Drying Time

Dependant upon thickness and atmospheric drying conditions. Typically 1 to 4 hours. NOTE - Patch material will reach optimum clarity after several days of curing.

Clean Up

Wash tools with water before material dries.

Weather Conditions

Do not apply if rain is imminent or forecast within 24 hours of application.

Coverage

Dependent upon depth and width of areas to be repaired.

Precautions

- Do Not Freeze
- Do Not Store at Temperatures Below 50 °F
- ATTENTION - Empty containers may retain material residues. Dispose of empty container in accordance with local, state, and federal regulations based upon chemical composition of contents

Safety And Environmental Precautions

- Refer to Material Safety Data Sheet Before Using
- For Exterior Application Only
- Close Container When Not in Use
- Environmental Information is on the Material Safety Data Sheet
- Do Not Reuse Empty Container
- Volatile Organic Content (VOC) is 100 gm/liter max
- KEEP OUT OF REACH OF CHILDREN

Ingredients:	Cas No.
Water	7732-18-5
100% Acrylic emulsion polymer	(proprietary)
Ester Alcohol	25265-77-4

Meets ASTM C920, Type S, NS (Non-Sag), Class 25.

Acrylic Clear-Drying Roof Patch

Revised: 01/19