

# Acrylic Clear Drying Roof Patch

Water-Based Paintable Formula



## Manufacturer:

ThorWorks Industries, Inc.  
2520 S. Campbell St.  
Sandusky, OH 44870  
Phone: 800-326-1994  
Fax: 419-626-5477

## Description

100% acrylic elastomeric water-based clear-drying roof patch.

## Uses

Adhering shingles, repairing cracks and seams on a variety of roof surfaces, vents, flashings, skylights, gutters, and more.

## Coverage

Dependent upon depth and width of areas to be repaired.

## Directions

**CLEAN ROOF-** Remove dust, dirt, debris, mildew and other contaminants from surface.

**APPLYING ROOF PATCH-** Apply Roof Patch with a trowel or putty knife.

## Drying Time

Dependant upon thickness and atmospheric drying conditions. Typically 1 to 4 hours. NOTE - Patch material will reach optimum clarity after several days of curing.

## Clean Up

Clean tools with water before material has dried.

## Important

Read entire label before using. Application temperature must be a minimum of 60 °F and rising. Do not apply when temperature is expected to drop below 60 °F within a 24 hour period. Be sure to wear eye protection, gloves, long pants, and long sleeves when mixing and applying SealBest materials. In areas where dew or fog accumulates in the early evening, it is best to coat in the morning. Stop coating by early afternoon (3:00 pm) to prevent wash off, which will occur if dew, fog, or rain arrive before coating dries. Do not apply if rain is imminent or forecast within 24 hours of application.

## Precautions

- Do Not Heat Or Thin
- Do Not Freeze
- Do Not Store At Temperatures Below 50 °F

## Safety And Environmental Precautions

- Refer To Material Safety Data Sheet Before Using
- For Exterior Use Only
- Apply In A Well Ventilated Area
- Close Container When Not In Use
- Environmental Information Is On The Material Safety Data Sheet
- Do Not Reuse Empty Container
- Volatile Organic Content (VOC) Is Less Than 100 Gm/Liter Max
- Keep Out Of Reach Of Children
- Avoid Breathing Vapors And Contact With Eyes And Skin. Do Not Take Internally
- Wear Eye Protection And Gloves When Applying

Ingredients:	CAS No.
Water	7732-18-5
100% Acrylic Emulsion Polymer	Proprietary
Ester Alcohol	25265-77-4

Acrylic Clear Drying Roof Patch

Revised: 01/11