

# Professional Grade Ultra Gloss Sealer

100% Acrylic Water-Based Formula



## Manufacturer:

ThorWorks Industries, Inc.  
2520 S. Campbell St.  
Sandusky, OH 44870  
Phone: 800-326-1994  
Fax: 419-626-5477

## Description

SealBest Ultra Gloss Sealer is a 100% Water-Based Acrylic Clear Sealer that provides a high gloss protective and durable finish to paving stone and exposed aggregate surfaces.

## Uses

Paving stone, decorative stone, and exposed aggregate concrete.

## Coverage

Approximately 130 - 170 square feet per gallon per coat

## Directions

**CLEAN SURFACE-** Sweep all dirt and loose debris from surface. Remove all oil, grease, and foreign materials. Surface must be completely dry before applying Ultra Gloss Sealer.

**APPLYING ULTRA GLOSS SEALER-** Stir pail thoroughly. Apply thin even coats of sealer with a roller. Additional coats may be applied to achieve desired level of gloss and finish. Allow material to dry thoroughly between coats.

## Drying Time

Up to 24 hours depending upon weather conditions.

## Clean Up

Wash tools with water before material dries.

## Important

Read entire label before using. Application temperature must be a minimum of 60 °F and rising. Do not apply when temperature is expected to drop below 60 °F within a 24 hour period. Be sure to wear eye protection, gloves, long pants, and long sleeves when mixing and applying SealBest materials. In areas where dew or fog accumulates in the early evening, it is best to coat in the morning. Stop coating by early afternoon (3:00 pm) to prevent wash off, which will occur if dew, fog,

or rain arrive before coating dries. Do not apply if rain is imminent or forecast within 24 hours of application.

## Precautions

- Do Not Heat Or Thin
- Do Not Freeze
- Do Not Store At Temperatures Below 50 °F

## Safety And Environmental Precautions

- Refer To Material Safety Data Sheet Before Using
- For Exterior Use Only
- Apply In A Well Ventilated Area
- Close Container When Not In Use
- Environmental Information Is On The Material Safety Data Sheet
- Do Not Reuse Empty Container
- Volatile Organic Content (VOC) Is 150 Gm/Liter Max
- Keep Out Of Reach Of Children
- Avoid Breathing Vapors And Contact With Eyes And Skin. Do Not Take Internally
- Wear Eye Protection And Gloves When Applying

Ingredients:	CAS No.
Water	7732-18-5
Acrylic Water Based Emulsion	Proprietary

Professional Grade Ultra Gloss Sealer

Revised: 01/11