

Professional Grade Concrete Patch

100% Acrylic Heavy-Bodied Formula



Manufacturer:

ThorWorks Industries, Inc.
2520 S. Campbell St.
Sandusky, OH 44870
Phone: 800-326-1994
Fax: 419-626-5477

Description

SealBest Concrete Patch is a 100% acrylic heavy-bodied trowel grade crack filler designed for filling larger cracks up to 1" wide in concrete surfaces. Concrete Patch can also be used to fill and repair damaged and spalled areas in concrete up to 1/4" deep.

Uses

Use to repair concrete driveways, floors, patios, sidewalks, pool decks, and more.

Coverage

Dependent upon depth and width of repair.

Directions

CLEAN CRACKS- Remove dirt and vegetation from cracks with screwdriver or other suitable instrument. Flush out crack with water and allow to dry.

DAMAGED AND SPALLED AREAS- Remove dirt and debris from repair area. Scrub thoroughly with wire brush and rinse with water.

APPLYING CONCRETE PATCH- Apply material with rectangular trowel or wide putty knife. Spread and smooth out material flush to adjoining surface.

Drying Time

Allow material to dry and cure for 48 hours prior to resuming foot or vehicle traffic.

Clean Up

Wash tools with water before material dries.

Important

Read entire label before using. Application temperature must be a minimum of 50 °F and rising. Do not apply when temperature is expected to drop below 50 °F within a 24 hour period. Be sure to wear eye protection, gloves, long pants, and long sleeves when mixing and applying SealBest materials. In areas where dew or fog accumulates in the early evening, it is best to coat in the

morning. Stop coating by early afternoon (3:00 pm) to prevent wash off, which will occur if dew, fog, or rain arrive before coating dries. Do not apply if rain is imminent or forecast within 24 hours of application.

Precautions

- Do Not Heat Or Thin
- Do Not Freeze
- Do Not Store At Temperatures Below 50 °F

Safety And Environmental Precautions

- Refer To Material Safety Data Sheet Before Using
- For Exterior Use Only
- Apply In A Well Ventilated Area
- Close Container When Not In Use
- Environmental Information Is On The Material Safety Data Sheet
- Do Not Reuse Empty Container
- Volatile Organic Content (VOC) Is 150 Gm/Liter Max
- Keep Out Of Reach Of Children
- Avoid Breathing Vapors And Contact With Eyes And Skin. Do Not Take Internally
- Wear Eye Protection And Gloves When Applying

Ingredients:	CAS No.
Water	7732-18-5
Acrylic Emulsion Polymer	Proprietary
Fiber	9004-34-6
Ester Alcohol	25265-77-4
Silicon Dioxide	14808-60-7

Professional Grade Concrete Patch

Revised: 01/11