

# Professional Grade Concrete Fortifier & Bonding Agent

Strong Acrylic Additive



## Manufacturer:

ThorWorks Industries, Inc.  
2520 S. Campbell St.  
Sandusky, OH 44870  
Phone: 800-326-1994  
Fax: 419-626-5477

## Description

A specially formulated Acrylic Additive designed to dramatically increase the strength of concrete, mortar, stucco, and other cement containing materials.

## Uses

Concrete, mortar, stucco, and other cement containing materials

## Coverage

Dependent upon dilution rate with water.

## Directions

**MIXING-** Stir contents before using.

**Concrete Patching:** Mix Concrete Fortifier full strength with dry concrete, mortar, stucco or other dry material.

**Bonding Agent:** Mix 2 parts Concrete Fortifier to 1 part water. Apply to slightly damp surface. Apply concrete or patching mixes immediately while the bonding agent is still wet. Caution: Do not allow bonding agent to dry before placing concrete or patching mixes over it.

## Drying Time

Allow mixes containing Concrete Fortifier to dry for 24 to 48 hours

## Clean Up

Wash tools with water before material dries.

## Important

Read entire label before using. Application temperature must be a minimum of 50 °F and rising. Do not apply when temperature is expected to drop below 50 °F within a 24 hour period. Be sure to wear eye protection, gloves, long pants, and long sleeves when mixing and applying SealBest materials. In areas where dew or fog accumulates in the early evening, it is best to coat in the morning. Stop coating by early afternoon (3:00 pm)

to prevent wash off, which will occur if dew, fog, or rain arrive before coating dries. Do not apply if rain is imminent or forecast within 24 hours of application.

## Precautions

- Do Not Heat Or Thin
- Do Not Freeze
- Do Not Store At Temperatures Below 50 °F

## Safety And Environmental Precautions

- Refer To Material Safety Data Sheet Before Using
- For Exterior Use Only
- Apply In A Well Ventilated Area
- Close Container When Not In Use
- Environmental Information Is On The Material Safety Data Sheet
- Do Not Reuse Empty Container
- Volatile Organic Content (VOC) Is 50 Gm/Liter Max
- Keep Out Of Reach Of Children
- Avoid Breathing Vapors And Contact With Eyes And Skin. Do Not Take Internally
- Wear Eye Protection And Gloves When Applying

Ingredients:	CAS No.
Water	7732-18-5
Acrylic Polymer	Proprietary

Professional Grade Concrete Fortifier & Bonding Agent

Revised: 01/11