

High Performance Driveway Patch

Heavy-Bodied Asphalt Patch



Manufacturer:

ThorWorks Industries, Inc.
2520 S. Campbell St.
Sandusky, OH 44870
Phone: 800-326-1994
Fax: 419-626-5477

Description

SealBest High Performance Driveway Patch is a heavy-bodied fast-drying asphalt emulsion fortified with mineral aggregate. It is designed for filling large cracks and small holes in asphalt pavement. Dries Black.

Uses

Fills and repairs large cracks and small holes in asphalt pavement.

Coverage

Ultimate coverage will be determined by depth and width of repair.

Directions

CLEAN CRACKS: Use a screwdriver, wire brush or other suitable tool to remove dirt, debris, and vegetation from cracks. Flush out cracks with hose and water. Allow cracks to dry prior to filling.

APPLICATION: Fill cracks, ruts, or depressions with SealBest High Performance Driveway Patch and trowel smooth. A rectangular trowel works best. Allow Driveway Patch to cure for 24 hours prior to applying SealBest Driveway Sealer.

Drying Time

Up to 24 hours depending upon weather conditions.

Clean Up

Wash tools with water before material dries.

Important

Read entire label before using. Application temperature must be a minimum of 60 °F and rising. Do not apply when temperature is expected to drop below 60 °F within a 24 hour period. Be sure to wear eye protection, gloves, long pants, and long sleeves when mixing and applying SealBest materials. In areas where dew or fog accumulates in the early evening, it is best to coat in the morning. Stop coating by early afternoon (3:00 pm) to prevent wash off, which will occur if dew, fog, or rain arrive before coating dries. Do not apply

if rain is imminent or forecast within 24 hours of application.

Precautions

- Do Not Heat Or Thin
- Do Not Freeze
- Do Not Store At Temperatures Below 50 °F

Safety And Environmental Precautions

- Refer To Material Safety Data Sheet Before Using
- For Exterior Application Only
- Apply In A Well Ventilated Area
- Close Container When Not In Use
- Environmental Information Is On The Material Safety Data Sheet
- Do Not Reuse Empty Container
- Volatile Organic Content (VOC) Is 100 Gm/Liter Max
- Keep Out Of Reach Of Children
- Avoid Breathing Vapors And Contact With Eyes And Skin. Do Not Take Internally
- Wear Eye Protection And Gloves When Applying

Ingredients:	CAS No.
Asphalt	8052-42-4
Clay	1332-58-7
Silica Sand	14808-60-7
Polymer Latex	Proprietary
Water	7732-18-5
Fiber	N/A

High Performance Driveway Patch

Revised: 01/11