

# Professional Grade Oil Spot Primer

Polymer Latex Emulsion Formula



## Manufacturer:

ThorWorks Industries, Inc.  
2520 S. Campbell St.  
Sandusky, OH 44870  
Phone: 800-326-1994  
Fax: 419-626-5477

## Description

SealBest Oil Spot Primer is a polymer latex emulsion designed to seal oil and gasoline stains prior to applying SealBest Driveway Sealer. Improves adhesion of driveway sealer to stained areas. Reduces the occurrence of oil bleeding through freshly applied sealer.

## Uses

Seals and primes oil and grease spots on asphalt driveways.

## Coverage

One .9 quart will cover approximately 30-50 square feet (one coat).

## Directions

**CLEAN OIL SPOTS:** Scrub oil and grease stains with stiff brush or broom, household detergent, and water. Rinse thoroughly with water.

**APPLICATION:** Mix contents of container by moderate shaking. Cut top of spout to allow material to flow out of container. Apply oil spot primer to stained areas. Spread with paint brush or other suitable brush. Allow oil spot primer to dry completely. A second coat of oil spot primer may be applied for added bleed through resistance. Oil Spot Primer must be completely dry before applying driveway sealer

## Clean Up

Wash tools with water before material dries.

## Drying Time

Typically, drying time is 1-2 hours.

## Important

Read entire label before using. Application temperature must be a minimum of 60 °F and rising. Do not apply when temperature is expected to drop below 60 °F within a 24 hour period. Be sure to wear eye protection, gloves, long pants, and long sleeves when mixing and applying SealBest materials. In areas where dew or fog accumulates

in the early evening, it is best to coat in the morning. Stop coating by early afternoon (3:00 pm) to prevent wash off, which will occur if dew, fog, or rain arrive before coating dries. Do not apply if rain is imminent or forecast within 24 hours of application.

## Precautions

- Do Not Heat Or Thin
- Do Not Freeze
- Do Not Store At Temperatures Below 40 °F

## Safety And Environmental Precautions

- Refer To Material Safety Data Sheet Before Using
- For Exterior Application Only
- Apply In A Well Ventilated Area
- Close Container When Not In Use
- Environmental Information Is On The Material Safety Data Sheet
- Do Not Reuse Empty Container
- Volatile Organic Content (VOC) Is 50 Gm/Liter Max
- Keep Out Of Reach Of Children
- Avoid Breathing Vapors And Contact With Eyes And Skin. Do Not Take Internally
- Wear Eye Protection And Gloves When Applying

Ingredients:	CAS No.
Polymer Latex	Proprietary
Water	7732-18-5

Professional Grade Oil Spot Primer

Revised: 01/11