

# Professional Grade All-Weather Roof Cement

Stops Roof Leaks Instantly



## Manufacturer:

ThorWorks Industries, Inc.  
2520 S. Campbell St.  
Sandusky, OH 44870  
Phone: 800-326-1994  
Fax: 419-626-5477

## Description

SealBest Professional Grade All Weather Roof Cement is the choice for professional satisfaction. This special blend of refined asphalts and adhesion promoters is designed to bond rapidly to moist, damp, wet or dry surfaces. It provides water repellency when conventional cements just won't stick. Dries Black.

## Uses

Can be used on flashings, vents, skylights, metal joints, seams, coping, and chimneys.

## Coverage

Approximately 12 square feet at 1/8" thick per gallon.

## Directions

**CLEAN AND REPAIR ROOF-** Clean surfaces thoroughly by brooming away all dirt, dust, and loose particulate. Nail down any loose parts.

**APPLYING ROOF COATING-** Stir pail thoroughly. Do not dilute. Using a trowel, spread SealBest All Weather Roof Cement onto the surface at a thickness of about 1/8", making sure to smooth down the edges. Mend cracks, splits, or blisters by troweling the cement to the affected area and three inches beyond. Embed SealBest Reinforcing Fabric into the repaired area and topcoat with another layer of roof patch material.

## Drying Time

Dry to the touch in 8 hours, depending upon weather conditions. Remains soft and pliable.

## Clean Up

Clean tools with mineral spirits before material has dried.

## Precautions

- Combustible. Contains Petroleum Distillate.
- Do Not Heat Or Thin
- Keep Away From Heat And Flame
- Do Not Store At Temperatures Above 100 °F

## Safety And Environmental Precautions

- Refer To Material Safety Data Sheet Before Using
- For Exterior Use Only
- Apply In A Well Ventilated Area
- Close Container When Not In Use
- Environmental Information Is On The Material Safety Data Sheet
- Do Not Reuse Empty Container
- Volatile Organic Content (VOC) Is 300 Gm/Liter Max
- Keep Out Of Reach Of Children
- Avoid Breathing Vapors And Contact With Eyes And Skin. Do Not Take Internally
- Wear Eye Protection And Gloves When Applying

Ingredients:	CAS No.
Asphalt	8052-42-4
Mineral Spirits	64742-88-7
Amine Salt	Not Est'd
Cellulose Fibers	9004-34-6
Attapulgate Clay	12174-11-7

Professional Grade All-Weather Roof Cement

Revised: 01/11